

VAC TRUCK HIRE

==== **MW**
HIRE



6300L VAC TRUCK INDUSTRIES HYDRO EXCAVATION TRUCK SPECIFICATIONS

SPOIL TANK AND BLOWER

6300L spoil tank capacity (10mm thickness)
Jurop style locking system for spoil tank door
Jurop PVT 400, high mercury, air injected – 1500cfm (28' Hg)
Jurop pneumatic 4-way valve – vacuum and pressure
Butterfly travel and relief valves

WATER TANK AND SYSTEM

2900L capacity – water tanks combined
Water tanks baffled for safety and stability
2' stainless steel water fill system with isolation taps
Water Level sight indicators on both tanks
Comet TW8036 water pump – 32l/m at 3600 psi
Heavy-duty hose reel complete with 25m 3/8
high-pressure water hose

HYDRAULIC SYSTEM

Dual PTOs with piston pumps
PTO with piston pump and Omsi split shaft assembly
Danfos PVG32 proportional control valve
170L oil tank with twin oil coolers

5" BOOM ASSEMBLY

Full hydraulic remote-controlled boom with 2 x lodar remotes
5" boom suction hose option
Plugin boom pendant control for an override of boom functions
2 x LED work lights mounted at the front of the boom

GENERAL

VTI full-length passenger side aluminium hose try storage –
with tie-down points and straps for load containment
Unique VTI driver side storage box for tooling and equipment with
integrated 3 lance holder box
Starter and battery isolation switches with lockout facility.
Emergency stops fitted in a key position on the tray
LED rotating lights and work lights fitted to the truck and spoil tank
Interlocks and warning alarms fitted to park brake, spoil tank, and boom
20m x 4' or 5' polyurethane vacuum hose with fittings of choice
9kg fire extinguisher with mounting bracket and notification decal
Full mine site compliant safety decals
Easy to clean baghouse and cyclone setup, accessible from the ground
Angled base on cyclone and baghouse for easy washout



MW
HIRE